

## E-LITE



|                                                                                                    |                                                                               |
|----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|
| <b>DESCRIZIONE PRODOTTO</b><br><i>PRODUCT DESCRIPTION</i><br><i>DESCRIPTION PRODUIT</i>            | LED signal light.                                                             |
| <b>STRUTTURA/STRUCTURE/STRUCTURE</b>                                                               | Base: PC;<br>Dome: PC Opaline;<br>OR: EPDM;<br>Connector M12/ Cable 2 poles . |
| <b>GRUPPO OTTICO</b><br><i>LUMINOUS SOURCE</i><br><i>SOURCE LUMINEUSE</i>                          | 14 Led                                                                        |
| <b>COLORI DISPONIBILI</b><br><i>AVAILABLE COLOURS</i><br><i>COULEURS DISPONIBLES</i>               | LED White, LED Green, LED Amber, LED Red; LED Blue.                           |
| <b>VOLTAGGIO/VOLTAGE/TENSION</b>                                                                   | 24 Vdc                                                                        |
| <b>SERVIZIO/OPERATION/FONCTIONNEMENT</b>                                                           | Continuous                                                                    |
| <b>CORRENTE NOMINALE</b><br><i>CURRENT CONSUMPTION</i><br><i>CONSOMMATION DE COURANT</i>           | 40 mA                                                                         |
| <b>INRUSH CURRENT</b><br><i>COURANT DE PIC</i>                                                     | 40 mA                                                                         |
| <b>RESA LUMINOSA</b><br><i>LIGHT OUTPUT</i><br><i>RENDMENT LUMINEUX</i>                            | 15 Cd(p) White                                                                |
| <b>MODALITA' LUCE</b><br><i>LIGHT EFFECT</i><br><i>EFFET LUMINEUX</i>                              | Steady light                                                                  |
| <b>RPM/FLASH-MIN</b><br><i>ROTATIONS OR FLASHES PER MINUTE</i><br><i>TOUR OU ECLATS PAR MINUTE</i> | ---                                                                           |
| <b>RESA ACUSTICA</b><br><i>SOUND OUTPUT</i><br><i>RENDMENT ACOUSTIQUE</i>                          | ---                                                                           |
| <b>GRADO IP/IP RATING/DEGRE IP</b>                                                                 | IP 66                                                                         |
| <b>GRADO IK/IK RATING/DEGRE IK</b>                                                                 | IK06                                                                          |

Dati diffusi a solo scopo informativo. Sirena S.p.A. puo' modificare i dati in qualsiasi momento senza preavviso.

These data are disclosed for information purposes. Sirena S.p.A. reserves the right to modify them at any time without prior notice.

Les données ne sont divulguées qu'à titre d'information. Sirena S.p.A. se réserve la faculté de les modifier à tout moment sans préavis



**SCHEDA TECNICA**  
**Technical data sheet**  
**Fiche technique**

03/04/19

**TEMPERATURA DI FUNZIONAMENTO**  
**OPERATING TEMPERATURE**  
**TEMPERATURE DE SERVICE**

-30+50°C

**VIBRAZIONI / VIBRATIONS / VIBRATIONS**

INDUSTRIAL CEI600-68-2-6

**CERTIFICAZIONI, OMOLOGAZIONI**  
**CERTIFICATIONS, APPROVALS**  
**CERTIFICATIONS, HOMOLOGATIONS**

CE

**FISSAGGIO / MOUNTING / FIXATION**

With screws on the base

**DISEGNO / TECHNICAL DRAWING / DESSIN**

