

GNEx Audible signals & PA loudspeakers

Zone 1 & 2 - Haz Loc.



GNExS1



GNExS2



GNExS1-R



GNExL1



GNExL2

These high-powered alarm horn sounders offer sound level outputs of up to 123dB(A) at 1 metre with a choice of 45 alarm tones and 4 remotely selectable stages.

The alarm tone frequencies for the first 2 stages are independently selectable. The unique radial horn presents a compact form and distributes the warning signal omni-directionally.

Also available are three versions of PA loudspeaker: 8 ohm or 16 ohm and 70V/100V Line transformer. On the 70V/100V line transformer units there are multiple output tappings for each version of loudspeaker.

Range Info:
Material Corrosion proof, glass-reinforced polyester.
Ingress Protection IP67
Fixings Stainless steel.
Mounting Ratchet adjustable stainless steel 'U' bracket.
Cable entries Dual M20 ISO. One stopping plug included.
Approvals: II 2G Ex d IIC T5 - Zone 1 & 2
ATEX, IECEx

Alarm Sounders/Horns
Ref: 1-22-010 GNExS1 Alarm Horn Sounder 10-30/38-60Vdc & 100-260Vdc/ac 50/60Hz. Max output: 117dB(A) @ 1m - 108dB(A) @ 10ft/3m 45 alarm tones with 4 stages/channels 182.7mm x 282.1mm (7.19" x 11.11")
Ref: 1-22-020 GNExS2 Alarm Horn Sounder 10-30/38-60Vdc & 100-260Vac 50/60Hz. Max output: 123dB(A) @ 1m - 114dB(A) @ 10ft/3m 45 alarm tones with 4 stages/channels 182.7mm x 332.5mm (7.19" x 13.09")

Radial Horn Alarm Sounder
Ref: 1-22-030 GNExS1-R Radial Alarm Sounder/Horn 10-30/38-60Vdc & 100-260Vdc/ac 50/60Hz. Max output: 117dB(A) @ 1m - 108dB(A) @ 10ft/3m 45 alarm tones with 4 stages/channels 182.7mm x 213.9mm (7.19" x 8.42")

PA Loudspeakers
Ref: 1-22-100 GNExL1 PA Loudspeaker 15W 70V/100V or 8 or 16 Ohm low impedance Rated SPL 113dB +/-3dB @ 15W @ 1m 182.7mm x 282.1mm (7.19" x 11.11")
Ref: 1-22-110 GNExL2 PA Loudspeaker 25W 70V/100V or 8 or 16 Ohm low impedance Rated SPL 119dB +/-3dB @ 25W @ 1m 182.7mm x 332.5mm (7.19" x 13.09")

