

GNEEx Manual Call Points

Zone 1 & 2 - Haz Loc.



GNEExCP6A-BG/GNEExCP6B-BG



GNEExCP6A-PB/GNEExCP6B-PB



GNEExCP6A-PT/GNEExCP6B-PT

The ATEX & IECEx approved GNEEx manual call point range is available in break glass, push button or tool reset versions. They are approved for Zone 1, 2, 21 and 22 hazardous areas for the control of fire and gas alarm systems.

All types are available with EOL or series resistors, diode or Zener diodes or an LED indicator and also with either single or double pole change over switches. The back box can be rotated to give one M20 side entry and dual M20 entries either at the top or bottom.

Range Info:

Material

Corrosion proof, glass-reinforced polyester.

Ingress Protection

IP66

Fixings

Stainless steel.

Cable entries

2 x M20 top and 1 x M20 side.

Stopping Plugs

2 x Ex e nylon plugs as standard.
Brass and stainless steel plugs optional.

Options

Alternative housing colours are available to meet specific requirements.
Single or double pole change over switch.
Metalised polyester or stainless steel "Duty" label.
Stainless steel lift flap for break glass model.

Approvals:

II 2G Ex e d IIC T6 Gb, II 2D Ex t IIIC T60°C Db
II 2G Ex e d mb IIC T4 Gb,
II 2D Ex t IIIC T80°C Db

ATEX, IECEx

Break Glass Call Points

Ref: 1-24-010

GNEExCP6A-BG Break Glass Call Point

120.0mm x 120.0mm x 79.0mm
4.73" x 4.73" x 3.11"

Ref: 1-24-020

GNEExCP6B-BG Break Glass Call Point (with EOL & series devices)

End of line and/or series monitoring resistors.
Diodes or Zener diodes or L.E.D. indicator.
Optional DIN rail mounted terminal blocks:
8 x 2.5mm².
120.0mm x 120.0mm x 79.0mm
4.73" x 4.73" x 3.11"

Push Button Call Points

Ref: 1-24-030

GNEExCP6A-PB Push Button Call Point

120.0mm x 120.0mm x 78.0
4 18/25" x 4 18/25" x 3"

Ref: 1-24-040

GNEExCP6B-PB Push Button Call Point (with EOL & series devices)

End of line and/or series monitoring resistors.
Diodes or Zener diodes or L.E.D. indicator.
Optional DIN rail mounted terminal blocks:
8 x 2.5mm².
120.0mm x 120.0mm x 79.0mm
4.73" x 4.73" x 3.11"

Tool Reset Call Points

Ref: 1-24-050

GNEExCP6A-PT Tool Reset Call Point

120.0mm x 120.0mm x 79.0mm
4.73" x 4.73" x 3.11"

Ref: 1-24-060

GNEExCP6B-PT Tool Reset Call Point (with EOL & series devices)

End of line and/or series monitoring resistors.
Diodes or Zener diodes or L.E.D. indicator.
Optional DIN rail mounted terminal blocks:
8 x 2.5mm².
120.0mm x 120.0mm x 79.0mm
4.73" x 4.73" x 3.11"

